

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23

CERTIFICATE OF EXPRESS MAILING

Express Mail label Number: EV 211810225 US
Date of Deposit: 6/25/03

I hereby certify that this paper is being deposited with the U.S. Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Name of Representative: Dean A. Craine

Signature: Dean A. Craine

TITLE: TRIMMER WHEELED EXTENSION ARM

This is a utility patent application which claims benefit of U.S. Provisional Application No. 60/469352 filed on May 9, 2003.

BACKGROUND OF THE INVENTION

1. Field of the Invention:

The present invention relates generally to the field of accessories that attach to string or line trimmers and, more particularly, to wheeled extensions that support line trimmers during use.

2. Description of the Related Art:

Several wheeled accessories that attach to a handheld electric or gas-powered line trimmers have been developed in the past (see U.S. Patent Nos. 4,531,350; 4,704,849; 4,829,755; 4,879,869; 4,891,931; 4,922,694; 5,092,112; and 5,228,276). All of these devices were developed to support a trimmer on wheels for easy mobility and to cut grass or weeds

1 evenly during use.

2 Line trimmers are used for a variety of applications in the yard. For example, they
3 function as mowing devices for cutting weeds and grass growing along fences or plants
4 where a lawnmower cannot reach. For these applications, the head of the trimmer must be
5 maintained horizontally so that the grass is cut evenly. Most of the trimmer wheeled
6 accessories include two wheels that extend laterally from the trimmer main pole. The wheels
7 are located between the head of the trimmer and the user thereby creating a fulcrum between
8 the trimmer head and the handle. The fulcrum requires the user to move the handle in an
9 opposite direction relative to the trimmer head during use.

10 The use of line trimmers to make a vertical cut around a lawn or hedge is also known.
11 Typically, this requires the user to manually hold the head of the trimmer so that the cutting
12 line or string cuts along a vertical path. When cutting a vertical edge around a lawn, it is
13 important to keep the cutting line or string on a vertical path and to position the distal end of
14 the line or string slightly above the soil line so that dirt and rocks are not thrown into the air.
15 Unfortunately, with prior art wheeled accessories that place two wheels behind the trimmer, it
16 is difficult to precisely control the trimmer head and practical use of a line-feed feature is
17 prohibited.

18 Another drawback of a trimmer wheeled accessory with two wheels located behind
19 and on opposite sides of the trimmer head is that the wheels extend laterally, preventing the
20 trimmer head from being positioned near or adjacent to another object or plant.

21 What is needed is one trimmer wheeled support accessory that addresses the need to
22 support the trimmer as it trims both horizontally and vertically, that is height adjustable, and
23 that enables the trimmer head to be placed close to plants or other objects.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a wheeled accessory that can be selectively attached to a line trimmer and allows the trimmer to roll over a surface.

It is another object of the present invention to provide a wheeled accessory that may support the line trimmer in both horizontal and vertical positions.

It is a further object of the present invention to provide a trimmer wheeled accessory that enables the user to easily adjust and maintain the height of the trimmer head while walking.

It is a further object of the present invention to allow for the normal operation of a line trimmer without removal or frequent adjustment of the trimmer wheeled extension arm.

It is a still further object of the present invention to allow the feed line feature of the trimmer to function with little or no interference from the trimmer wheeled accessory.

These and other objects of the present invention are met by a trimmer wheeled accessory for a handheld, portable, gas or electric powered, line trimmer that selectively attaches to the trimmer main pole. The accessory includes an extension arm that extends longitudinally and distally from the trimmer head to support the trimmer head on the ground during operation. The extension arm includes an adjustable first clamp member used to attach the extension arm to approximately the main pole. The first clamp member allows the length of the extension arm that extends beyond the trimmer head to be adjusted. The first clamp member also allows the extension arm to axially rotate and laterally pivot around the main pole. The axial rotation feature allows the user to align the trimmer head for either vertical or horizontal cutting. Attached to the distal end of the extension arm is a wheel assembly that supports and allows the distal end of the extension pole to roll on the ground or

1 grass. When the accessory is attached to the main pole, the fulcrum for the line trimmer is
2 located in front of the trimmer head. This feature provides greater control for the user. In the
3 preferred embodiment, the wheel assembly is able to rotate freely 360 degrees. An optional
4 clamp member may be provided between the wheel assembly and the distal end of the
5 extension arm that enables the wheel assembly to selectively rotate and lock in different
6 positions during use. This feature is especially useful when the user wants to align the
7 trimmer head in an offset position relative to the path of the wheel assembly.

8 The extension arm also includes an optional second clamp member that allows the
9 length of the extension arm relative to the main pole to be adjusted. The second clamp
10 member also allows adjustment of the forward and aft angular orientation of the extension
11 pole relative to the main pole. The axis of rotation of the second clamp member is
12 perpendicular to the axis of rotation of the first clamp member. By allowing adjustment of the
13 forward and aft orientation of the extension pole, the relative pitch of the extension pole on
14 the main pole may be adjusted so that the trimmer head may be maintained at the desired
15 cutting height as the trimmer is moved.

17 DESCRIPTION OF THE DRAWINGS

18 Fig. 1 is a perspective view of the trimmer wheeled accessory arm attached to a line
19 trimmer.

20 Fig. 2 is a top plan view of the trimmer wheeled accessory shown in Fig. 1.

21 Fig. 3 is a front elevational view of the trimmer wheeled accessory.

22 Fig. 4 is a rear elevational view of the trimmer wheeled accessory.

23 Fig. 5 is a perspective view of the bracket used to attach the wheel assembly to the

1 distal end of the extension arm.

2 Fig. 6 is a right side elevational view of the bracket shown in Fig. 5.

3 Fig. 7 is a perspective view of the axle support on the wheel assembly.

4 Fig. 8 is a side elevational view of the L-shaped coupler with the second and third
5 clamp members attached thereto.

6 Fig. 9 is an end elevational view of the L-shaped coupler shown in Fig. 8.

7 Fig. 10 is a side elevational view of a clamp member.

8 Fig. 11 is a top plan view of the lower strap housing shown in Fig. 10.

9

10 **DESCRIPTION OF THE PREFERRED EMBODIMENT(S)**

11 Shown and described in the accompanying Figs. is a trimmer wheeled accessory 8 for
12 a handheld, portable, gas- or electric-powered line trimmer 90 that selectively attaches to the
13 trimmer's main pole 92. The accessory 8 includes an elongated extension arm 10 that
14 extends longitudinally and distally from the trimmer head 94 to support the trimmer head 94
15 on the ground during operation. The extension arm 10 includes an adjustable first clamp
16 member 20 used to attach the extension arm 10 to approximately the middle section on the
17 main pole 92. The first clamp member 20 allows the length of the extension arm 10 that
18 extends beyond the trimmer head 94 to be adjusted to place the trimmer head 94 at different
19 elevations during use. The first clamp member 20 also allows the extension arm 10 to axially
20 rotate to align the trimmer head 94 in either a vertical or horizontal orientation. The first
21 clamp member 20 also allows the extension arm 10 to pivot laterally around the main pole 92
22 as shown in Fig. 2.

23 In the preferred embodiment, the first clamp member 20 includes a lower clamp

1 member 23 with adjustable strap 22 that attaches to the main pole 92 via the adjustable U-
2 shaped strap 22. Attached to the lower clamp member 23 is a rotating upper clamp member
3 21. Disposed between the lower clamp member 23 and upper clamp member 21 is a handle
4 25 and center post 26 that interconnects with the strap 22 to tighten or loosen the strap 22
5 around the main pole 92. A more detailed description of the first clamp member 20 is
6 discussed below.

7 Attached to the distal end 11 of the extension arm 10 is a wheel assembly 50 that
8 supports and allows the distal end 11 of the extension arm 10 to roll on the ground or grass.
9 The wheel assembly 50, shown more clearly in Figs. 3, 5 – 7, includes an upper adapter 52
10 that securely attaches to the distal end 11 of the extension arm 10. Rotatingly attached to the
11 upper adapter 52 is a lower adapter 56. Formed on the lower adapter 56 are two downward
12 extending wings 57, 57'. An axle 60 is transversely aligned between the two downward
13 extending wing members 57, 57' and two wheels 65, 67 are attached to the axle 60. In the
14 preferred embodiment, a locking member 40 is attached to the wheel assembly 50 that
15 enables the user to lock the wheel assembly 50 in a fixed position on the extension arm 10.
16 The locking member 40 includes a handle 45 with a center post 46 that extends through the
17 upper and lower adapters 52, 56 and connects to a nut 47 located under the top flange
18 member 58 on the lower adapter 56. During use, the locking member 40, center post 46, and
19 nut 47 hold the adapters 52, 56 together and enable the lower adapter 56 to freely rotate under
20 the upper adapter 52. During use, the handle 45 is manually opened and closed so that the
21 lower adapter 56 may be selectively rotated or locked in position under the upper adapter 52
22 to change the orientation of the wheels 65, 67. By changing the orientation of the wheels 65,
23 67, the trimmer head 94 may be aligned in an offset position relative to the directional path of

1 the wheel assembly 50 during use.

2 Disposed between the first clamp member 20 and the proximal end 12 of the
3 extension arm 10 is an optional second clamp member 30 that allows the angular orientation
4 of the extension arm 10, relative to the main pole 92, to be adjusted. In the preferred
5 embodiment, the first and second clamp members 20, 30 are perpendicularly aligned on an L-
6 shaped bracket 68. As shown in Figs. 8 and 9, the L-shaped bracket 68 supports both the first
7 and second clamp members 20, 30, respectively, when they are attached to the main pole 92
8 and extension leg 10. Formed on one end of the bracket 68 is a first support flange 69 upon
9 which said first clamp member 20 is located. On the opposite end of the bracket 68 is a
10 second support flange 70 upon which the second clamp member 30 is located. The first and
11 second support flanges 69, 70, respectively, are perpendicularly oriented to each other.

12 The first and second clamp members 20 and 30 are identical and are similar to the
13 locking member 40 used on the wheel assembly 50. As shown in Figs. 10 and 11, the clamp
14 member 20 includes a pivoting handle 25 attached to the end of a threaded center post 26.
15 The center post 26 extends into an upper and lower clamp member 21, 23, respectively. The
16 distal end of the center post 26 connects to a rod 96. Formed on the rod 96 is a threaded,
17 transversely aligned bore 97. The rod 96 extends transversely over a U-shaped strap 22 that
18 mounts inside the lower clamp member 23. The strap 22 extends downward from an opening
19 24 formed on the lower clamp member 23 and around the main pole 92 to connect the lower
20 clamp member 23 thereon. The upper and lower clamp members 21, 23 are cylindrical and
21 include ring structures 89, 91, respectively, with teeth formed thereon. During assembly, the
22 upper and lower clamp members 21, 23 are longitudinally aligned so that the teeth mesh to
23 lock the upper and lower clamp members 21, 23 together. During use, the handle 25 is

1 rotated to release pressure on the center post 26 and strap 22 so that the strap 22 may be
2 moved longitudinally or rotated around the main pole 92. Simultaneously, the user may
3 rotate the upper clamp member 21 to reposition the handle 25 for easier operation.

4 In the preferred embodiment, the extension arm 10 is made of aluminum and
5 measures approximately 18 inches in length and 3/4 inches in diameter. The wheels 65, 67
6 are approximately 2 inches in diameter and approximately 3 to 7 inches apart when attached
7 to the axle 60.

8 During use, the extension arm 10 is selected and the first clamp member 20 is
9 attached to the main pole 92 so that the wheel assembly 50 is positioned a sufficient distance
10 in front of the trimmer head 94 to position the trimmer head 94 at the proper elevation. If
11 the second clamp member 30 is used, then the first clamp member 20 is positioned
12 proximally approximately 6 to 12 inches behind the trimmer head 94. Once the initial
13 location of the first clamp member 20 is determined, the extension arm 10 is then rotated
14 over the main pole 92 so that the extension arm 10 is disposed either above or on one side of
15 the main pole 92. The handle 25 is then tightened to lock the first clamp member 20 in
16 position on the main pole 92.

17 The third clamp member 30 is then used to adjust the orientation of the wheel
18 assembly 50.

19 If a second clamp member 30 is used, the second clamp member 30 is manipulated to
20 finely adjust the orientation of the wheel assembly 50 relative to the trimmer head 94. As
21 mentioned above, the second clamp member 30 allows the user to change the pitch of the
22 extension arm 10 relative to the main pole 92. This adjustment feature allows users with
23 different standing heights to adjust the pitch of the extension arm 10 so that the trimmer head

1 94 cuts evenly when the wheel assembly 50 is pushed or pulled over a support surface.

2 In compliance with the statute, the invention described herein has been described in
3 language more or less specific as to structural features. It should be understood, however,
4 that the invention is not limited to the specific features shown, since the means and
5 construction shown is comprised only of the preferred embodiments for putting the invention
6 into effect. The invention is therefore claimed in any of its forms or modifications within the
7 legitimate and valid scope of the amended claims, appropriately interpreted in accordance
8 with the doctrine of equivalents.

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23